

IOP 245_Tracking of Dissolved Effluent Organic Matter (dEfOM) in wastewater treatment plant by using fluorescence method

by Euis Nurul Hidayah

Submission date: 23-Nov-2020 11:28AM (UTC+0700)

Submission ID: 1454636961

File name: Kinerja_IOP_EES_245.pdf (788.44K)

Word count: 2772

Character count: 16510

PAPER · OPEN ACCESS

Tracking of Dissolved Effluent Organic Matter (dEfOM) in wastewater treatment plant by using fluorescence method

To cite this article: E N Hidayah and O H Cahyonugroho 2019 *IOP Conf. Ser.: Earth Environ. Sci.* **245** 012018

View the [article online](#) for updates and enhancements.

Tracking of Dissolved Effluent Organic Matter (dEfOM) in wastewater treatment plant by using fluorescence method

E N Hidayah and O H Cahyonugroho

Department of Environmental Engineering, University of Pembangunan Nasional
"Veteran" Jawa Timur, Raya Rungkut Madya, Gunung Anyar, Surabaya, Indonesia

Email: euisnh@gmail.com

Abstract. Discharge of wastewater into water body can change the quantity and quality of natural organic matter (NOM) in source water, because wastewater may contain dissolved effluent organic matter (dEfOM). dEfOM consists of a heterogenous mixture of organic compounds with various structures, such as dissolved organic matter, microbial by-products, endocrine disrupting compound, etc. The objectives of this study is to track the fate of dEfOM by using fluorescence excitation emission matrices (FEEMs) in order to apply of reclaimed water from industrial wastewater. Tracking of NOM was observed in industrial park of wastewater treatment, which is consist of equalization tank, coagulation, flocculation, sedimentation, activated sludge tank and clarifier tank. FEEMs with parallel factor analysis (PARAFAC) analysis decomposed the organic matter in wastewater into two components, namely component C1 at (Ex/Em): 330(235)/410 is humic acid like and fulvic, component C2 at (Ex/Em): 280(230)/350 is soluble microbial products and aromatic protein. Characteristic of dEfOM depends on the wastewater characteristic and its treatment processes.

1. Introduction

Discharging of effluent from treated wastewater is an one of the contributed source of organic matter to aquatic systems. The contribution of organic matter from wastewater effluent discharge severely affects water quality, particularly in water treatment processes. The sustained increase in quantity and quality of organic matter in raw water will decrease the performance of water treatment processes and add the advanced technology of water purification, such as dosage increasing for coagulant, oxidant, disinfectant, and also membrane fouling, decreasing adsorption capacity of activated carbon [1]. Effluent organic matter (EfOM) is the organics in the sewage that cannot be removed during wastewater treatment. Constituents of EfOM in wastewater can be classified as synthetic organic compounds and microbial by-products derived from biological wastewater treatment processes. EfOM are typically cell fragments and macromolecules, such as polysaccharides, proteins, lipids, carbohydrates, amino acids, vitamins and chlorophyll [2].

EfOM from different types of wastewater could have various compounds, which differ from terrestrial organic matter. Component hydrophobic and transphilic of EfOM are derived from microbial sources, EfOM contains between 60-80% hydrophilic material [3]. Coagulation, flocculation, sedimentation and rapid sand filtration is mostly used and feasible method to treat organic matter. The remaining organic matter can be further removed by advanced treatment processes, such as adsorption with activated carbon [4], biofiltration, ion exchange [5], pellet softening

[6], ozonation [7], membrane technology [8], advanced oxidation process (AOP), such as hydroxyl radical.

Combined treatment process and hybrids with different combination of those mentioned methods have been employed for removal of EfOM. The objective of these combined systems is to maximise the removal of different fractions of the NOM. Some of these methods include: coagulation followed by ultrafiltration, ozonation followed by granular activated carbon, activated carbon filter followed by reverse osmosis, biofiltration followed by nanofiltration, ion exchange followed by activated carbon filtration and ozonation followed by biofiltration and membrane processes [6,9]. However, some researchs showed that the biological treatment processes will produce soluble microbial products (SMPs) and extracellular polymeric substances (EPS) material [10,11]. Several research projects had investigated using biological processes or combined chemical processes with biological processes to remove organic matter [12,13].

Several methods for organic matter composition and structure have been developed in the last decades, such as NMR, FTIR, HPSEC, EEM spectroscopy, which detect organic matter based on their properties [14]. Nevertheless, characterization of EfOM in wastewater plant in Indonesia and concern to water reuse or wastewater reclamation is still a few. Therefore, an interest in characterizing EfOM has become more important.

2. Research Method

Wastewater effluent was collected from wastewater treatment plant of industrial park. The wastewater treatment train include inlet chamber, equalization tank, coagulation, flocculation, sedimentation, activated sludge tank, clarifier and indicator pond. Sample was taken in each effluent unit process twice per-week for one month. As this study focused on characterization of EfOM, the collected effluent wastewater was filtered through 1.2/0.5 μm and 0.45 μm disposable capsule filters (both from Millipore Corporation, USA) to remove any suspended solids before further usage.

Wastewater effluent samples were analysed for bulk parameter characteristics, including dissolved organic carbon (DOC) by using a total organic carbon analyzer (Model TOC-5000A, Shimadzu, Japan), ultraviolet absorbance at wavelength 254 nm (UV_{254}) by using a UV-VIS spectrophotometer (Model UV-2600, Shimadzu, Japan), and pH measurement [15].

Fluorescence measurements have been undertaken using a Perkin Elmer LS-55 luminescence spectrometer was used to measure fluorescence signal with excitation wavelengths 200-400 nm at 10-nm and emission wavelength 2.5-nm increment from 300 to 547.5 nm. EEMs were measured using 1-cm path length quartz cells. EEM of Milli-Q water samples was collected throughout the experiment period. Water Raman scatter peak were eliminated by subtracting the EEMs of Milli-Q water blank and normalized to the area under the water Raman peak of the blank at excitation wavelength 350 nm, producing data in Raman Units (R.U.).

PARAFAC analysis applied all EEM datasets fluorescence, which uses an alternating least-square algorithm to decompose the data signal into a set of trilinear terms and a residual array, as described with:

$$x_{ijk} = \sum_{f=1}^F a_{if} b_{jf} c_{kf} + e_{ijk} \quad i = 1, 2, \dots, I; j = 1, 2, \dots, J; k = 1, 2, \dots, K; f = 1, 2, \dots, F$$

where x_{ijk} is fluorescence intensity of the i th samples at the j th variable (emission mode) and at k th variable (excitation mode); a_{if} is the concentration of the f th analyte in the i th sample; b_{jf} is the fluorescence quantum efficiency of the n th analyte at emission wavelength j ; c_{kf} is the specific absorption coefficient at excitation wavelength k ; F is the number of fluorophores (components) and e_{ijk} is the residual noise, representing the variability not accounted for by the model [16]. drEEM toolbox in Matlab® (<http://www.models.life.ku.dk/drEEM>) [17], was used to generate parallel factor analysis (PARAFAC) models.

3. Result and Discussion

3.1. Bulk wastewater quality for industrial wastewater treatment train

Figure 1 shows the variation of organic matter surrogates in term of DOC concentration, UV₂₅₄ and SUVA value of treated wastewater in each unit process. The variation was more pronounced for the treatment by coagulation, flocculation, sedimentation, and activated sludge processes. Unit process of inlet chamber and equalization tank has the highest value, while the effluent of sedimentation has the lowest value for organic carbon and UV₂₅₄. It indicated that aromatic pro[22], which composed organic carbon in wastewater, are more amenable to be removed in the physical treatment, such as coagulation, flocculation and sedimentation. It is consistent with that reviewed in the previous study [18,19].




Figure 1. The variation of DOC, UV₂₅₄, and SUVA value of effluent wastewater treatment of industrial park.

Figure 2 shows the percentage reduction of organic matter TOC, UV₂₅₄ and SUVA value across the wastewater treatment processes. The general trend is a reduction in DOC through equalization, coagulation, flocculation, sedimentation, and insignificantly removal in clarifier after activated process and in the indicator pond. Activated sludge process could increase the organic compound, which represented through increasing DOC and UV₂₅₄ concentration. In addition, biological process could degrade hydrophobic and hydrophilic compound as detected by SUVA value. Biological processes, which involved microbiology for biodegradation, could release organic matter, such as soluble microbial products (SMPs) as by-product during their metabolism processes. SMPs will be derived during substrate utilization and may released from cell lysis during biomass decay [20].




Figure 2. The changing of DOC, UV₂₅₄, and SUVA value of effluent wastewater treatment of industrial park in every sampling unit.

17
 3.2. Using Fluorescence Excitation-Emission Matrices (F-EEMs) to Characterize dEfOM Contained
 1 the Wastewater 21

Parallel Factor Analysis (PARAFAC) was needed to model the dataset of fluorescence excitation emission matrices (F-EEMs). The specific 6 data set with non-negativity constraints were used on all modes during preprocessing dataset. The F-EEMs were also Raman calibrated by normalizing to the area under the Raman scatter peak of Milli-Q water samples, in order to remove scatter. Measurement at excitation wavelengths below 220 nm were excluded, because 2 5 samples were identified by leverage plots (about 9% of 56 samples) as outlier. Each dataset was normalized to its total signal before PARAFAC modelling in order 20 to reduce correlation between components. After preprocessing, PARAFAC modelling was applied for each data. A series of PARAFAC models consisting of 2 components were generated and those number of fluorescence components was validated using split half analysis and split half validation. Finally, PARAFAC analysis decomposed the organic matter in treated wastewater into two components, as shown in Figure 3.




Figure 3. Fluorescence (a) Component 1 and (b) Component 2 have been found from effluent of wastewater treatment in industrial park.

The fluorescence components in this study are comparable with previously classified components [21,22]. The component C1 comprises two peaks centered at excitation/emission (Ex/Em): 230/410 nm, which is identified as fulvic acid-like and also as the main peak, the second 5 peak of component C2 at (Ex/Em): 330/410 nm, as humic acid-like. The component C2 had first and secondary excitation peak, about 280 nm and 230 nm, respectively, and with single emission peak about 350 nm, and it is

identified as soluble microbial products (SMPs) and aromatic protein, respectively. Further, the component distribution in the source and treated water was described in terms of Fmax in order to attempt the relative contribution of the PARAFAC fluorophore to the tracking of dissolved organic matter. However, the higher Fmax does not indicate a major existence of the component in the all sample [23].

Effluent of wastewater treatment was composed of fluorescence soluble microbial products as dominant component and followed by humic acid-like and aromatic protein. The presence of those component probably contributed by the biological activities which released their metabolite products. Previous studies have mentioned that biological process might release organic compound during metabolism and decay [20], whether as extracellular polymeric substances (EPS), SMPs, and inert biomass [10].

4. Conclusion

This study concludes that FEEMs analysis revealed that two component, (Ex/Em): 230/410 nm; (Ex/Em): 330/410 nm, derived from PARAFAC modelling were the major organic component in effluent wastewater from industrial park. F-EEMs and dEfOM bulk parameter demonstrated that wastewater treatment train had applied, significantly reduced the aromaticity of organic carbon matter in water. Coagulation-flocculation and sedimentation removed organic carbon significantly. Biological process gives higher contribution to the existence of dEfOM than other processes.

5. Acknowledgment

The financial support provided for this study by the Department of Environmental Engineering, University of Pembangunan Nasional Veteran Jawa Timur, Indonesia is greatly appreciated.

References

- [1] Matilainen, A., Iivari, P., Sallanko, J., Heiska, E., & Tuhkanen, T. 2006. The role of ozonation and activated carbon filtration in the natural organic matter removal from drinking water, *Environmental Technology*, 27, 1171–1180.
- [2] Edzwald, J.K., & Tobiasson, J.E. 2011. Chemical Principles, Source Water Composition, and Watershed Protection. In *Water Quality & Treatment: A Handbook on Drinking Water*, Edzwald, J.K., Eds., New York: AWWA McGraw-Hill, 1-76.
- [3] Quaranta, M.L., Mendes, M.D., & MacKay, A.A. 2012. Similarities in effluent organic matter characteristics from Connecticut wastewater treatment plants, *Water Research*, 46, 284-294.
- [4] Velten, S., Detlef R.U. Knappeb, Traber, J., Kaiser, H.P., Gunten, U., Bollner, M., & Meylan, S. 2011. Characterization of natural organic matter adsorption in granular activated carbon adsorbers, *Water Research*, 45, 3951-3959.
- [5] Cornelissen, E.R., Moreau, N., Siegers, W.G., Abrahamse, A.J., Rietveld, L.C., Grefte, A., Dignum, M., Amy, G., & Wessels, L.P. 2008. Selection of anionic exchange resins for removal of natural organic matter (NOM) fractions. *Water Research*, 42, 413-423.
- [6] Grefte, A., Dignum, M., Kroesbergen, J., & Cornelissen, E.R. 2011. The Effect of changing NOM composition, measured by LC-OCD, on NOM treatability in downstream processes. Speciality Conference on Natural Organic Matter, Costa Mesa, CA, USA, July 27-29.
- [7] Kasprzyk-Hordern, B., Raczek-Stanislawiak, Swietlik, J., & Nawrocki, J. 2005. Catalytic ozonation of natural organic matter on alumina, *Applied Catalysis*, 62, 345-358.
- [8] Kennedy, M. D., Chun, H.K., Yangali, V.A.K., Heiman, B.G.J., & Schippers, J.C. 2005. Natural organic matter (NOM) fouling of ultrafiltration membranes: fractionation of NOM in surface water and characterization by LC-OCD, *Desalination*, 178, 73-83.
- [9] Chen, C., Zhang, X. J., Zhu, L. X., Liu, J., He, W.J., & Han, H. 2011. Changes in different organic matter fractions during conventional treatment and advanced treatment. *Journal of Environmental Sciences*, 23(4), 582–586.
- [10] Lapidou C.S., & Rittmann, B.E. 2002. A unified theory for extracellular polymeric substances,

- soluble microbial products, and active and inert biomass, *Water Research*, 36, 2711–2720.
- [11] Jang, N., Ren X., Kim, G., Ahn, C., Cho, J., & Kim, S. 2006. Characteristics of soluble microbial products and extracellular polymeric substances in the membrane bioreactor for water reuse, *Desalination*, 202, 90–98.
- [12] Yapsakliä, K., Mertoglub, B. & Cecen, F. 2010. Identification of nitrifiers and nitrification performance in drinking water biological activated carbon (BAC) filtration, *Process Biochemistry*, 45, 1543–1549.
- [13] Saeedi, R. Naddafi, K., Nabizadeh, R., Mesdaghinia, A., Nasserli, S., Alimohammadi, M., & Nazmara, S. 2012. Simultaneous removal of nitrate and natural organic matter from drinking water using a hybrid heterotrophic/autotrophic/biological activated carbon bioreactor, *Environmental Engineering Science*, 29(2), 93-100.
- [14] Sillanpää, M., Matilainen, A. & Lahtinen, T. 2015. Characterization of NOM. In *Natural Organic Matter in Water: Characterization and Treatment Method*; Silanpää, M., Eds., Oxford: England, Butterworth-Heinemann, 17–53.
- [15] APHA, AWWA, & WEF. 2012. *Standard Methods for the Examination of Water and Wastewaters*. 21th ed., Washington, D.C., USA: American Public Health Association
- [16] Stedmon, C.A., Markager, S. & Bro, R. 2003. Tracing dissolved organic matter in aquatic environments using a new approach to fluorescence spectroscopy, *Marine Chemistry*, 82, 239-254.
- [17] Murphy, K.R., Stedmon, C.A., Graeber, D. & Bro, R. 2013. Fluorescence spectroscopy and multi-way techniques. *PARAFAC, Analytical Methods*, 5 (23), 6557-6566.
- [18] Matilainen, A., Vepsäläinen, M., & Silanpää, M. 2010. Natural organic matter removal by coagulation during drinking water treatment: a review, *Advances in Colloid and Interface Science*, 159, 189-197.
- [19] Hidayah E.N., Chou, Y. C., & Yeh, H.H. 2016. Using HPSEC to identify NOM fraction removal and the correlation with disinfection by-product precursors. *Water Science and Technology*, 16 (2), 305-313.
- [20] Ni, B.J., Rittmann, B.E., & Yu, H.Q. 2011. Soluble microbial products and their implications in mixed culture biotechnology, *Trends Biotechnology*, 29, 454-463.
- [21] Yu, H., Liang, H., Qu, F., Han, Z.S., Shao, S., Chang, H. & Li, G. 2015. Impact of dataset diversity on accuracy and sensitivity of parallel factor analysis model of dissolved organic matter fluorescence excitation-emission matrix, *Scientific Reports*, 5, 1–10
- [22] Hidayah E.N., Chou, Y. C., & Yeh, H. H. 2017. Comparison between HPSEC-OCD and F-EEMs for assessing DBPs formation in water. *Journal of Environmental Science and Health Part A*, 52(4), 391-402.
- [23] Sanchez, N. P., Skeriotis, A.T. & Miller, C. M. 2013. Assessment of dissolved organic matter fluorescence PARAFAC components before and after coagulation–filtration in a full scale water treatment plant, *Water Research*, 47, 1679-1690.

IOP 245_Tracking of Dissolved Effluent Organic Matter (dEfOM) in wastewater treatment plant by using fluorescence method

ORIGINALITY REPORT

22%

SIMILARITY INDEX

17%

INTERNET SOURCES

16%

PUBLICATIONS

2%

STUDENT PAPERS

PRIMARY SOURCES

1

repository.tudelft.nl

Internet Source

3%

2

www.nature.com

Internet Source

2%

3

serc.si.edu

Internet Source

2%

4

Sanchez, Nancy P., Andrew T. Skeriotis, and Christopher M. Miller. "Assessment of dissolved organic matter fluorescence PARAFAC components before and after coagulation–filtration in a full scale water treatment plant", *Water Research*, 2013.

Publication

1%

5

Guocheng Zhu, Jun Yin, Peng Zhang, Xiaofeng Wang, Gongduan Fan, Bin Hua, Bozhi Ren, Huaili Zheng, Baolin Deng. "DOM removal by flocculation process: Fluorescence excitation–emission matrix spectroscopy (EEMs) characterization", *Desalination*, 2014

1%

6

researchbank.rmit.edu.au

Internet Source

1%

7

Colin A. Stedmon, David N. Thomas, Mats Granskog, Hermanni Kaartokallio, Stathys Papadimitriou, Harri Kuosa. "Characteristics of Dissolved Organic Matter in Baltic Coastal Sea Ice: Allochthonous or Autochthonous Origins?", *Environmental Science & Technology*, 2007

Publication

1%

8

Yijing Zhu, Lijuan Cao, Lingfeng Ni, Yayi Wang. "Insights into fouling behavior in a novel anammox self-forming dynamic membrane bioreactor by the fluorescence EEM-PARAFAC analysis", *Environmental Science and Pollution Research*, 2020

Publication

1%

9

Peng Li, Nuerla Ailijiang, Xiaoxin Cao, Ting Lei, Peng Liang, Xiaoyuan Zhang, Xia Huang, Jilin Teng. "Pretreatment of coal gasification wastewater by adsorption using activated carbons and activated coke", *Colloids and Surfaces A: Physicochemical and Engineering Aspects*, 2015

Publication

1%

10

Lai, Chun-Hsi, Yung-Chen Chou, and Hsuan-Hsien Yeh. "Assessing the interaction effects of

1%

coagulation pretreatment and membrane material on UF fouling control using HPSEC combined with peak-fitting", Journal of Membrane Science, 2015.

Publication

11

Matthew L. Quaranta, Mykel D. Mendes, Allison A. MacKay. "Similarities in effluent organic matter characteristics from Connecticut wastewater treatment plants", Water Research, 2012

Publication

1%

12

www.science.gov

Internet Source

1%

13

www.tandfonline.com

Internet Source

1%

14

ir.lib.uwo.ca

Internet Source

1%

15

dspace.cc.tut.fi

Internet Source

1%

16

Submitted to University of South Australia

Student Paper

1%

17

etds.lib.ncku.edu.tw

Internet Source

1%

18

Andy Baker. "Fluorescence Excitation–Emission Matrix Characterization of Some Sewage-

<1%

Impacted Rivers", Environmental Science & Technology, 2001

Publication

19

Zhuo Zeng, Ping Zheng, Aqiang Ding, Meng Zhang, Ghulam Abbas, Wei Li. "Source analysis of organic matter in swine wastewater after anaerobic digestion with EEM-PARAFAC", Environmental Science and Pollution Research, 2017

Publication

<1%

20

www.researchgate.net

Internet Source

<1%

21

Stedmon, C.A.. "Tracing dissolved organic matter in aquatic environments using a new approach to fluorescence spectroscopy", Marine Chemistry, 200308

Publication

<1%

22

Tahir Maqbool, Yanling Qin, Quang Viet Ly, Jiaxing Zhang, Chengyue Li, Muhammad Bilal Asif, Zhenghua Zhang. "Exploring the relative changes in dissolved organic matter for assessing the water quality of full-scale drinking water treatment plants using a fluorescence ratio approach", Water Research, 2020

Publication

<1%

23

Angélique Goffin, Sabrina Guérin, Vincent Rocher, Gilles Varrault. "Towards a better

<1%

control of the wastewater treatment process:
excitation-emission matrix fluorescence
spectroscopy of dissolved organic matter as a
predictive tool of soluble BOD5 in influents of six
Parisian wastewater treatment plants",
Environmental Science and Pollution Research,
2018

Publication

Exclude quotes Off

Exclude matches Off

Exclude bibliography On