



## DAFTAR PUSTAKA

- Bandyopadhyay , A. and Biswas , M.N. 2007 . “Fly ash scrubbing in a novel dual flow scrubber” . *Waste Manage* , 27 : 1845 – 1859
- Budiman, A 2014, ‘Analisis Perpindahan Panas Dan Efisiensi Efektif High Pressure Heater (HPH) Di PLTU Asam–Asam’, *Jurnal Ilmiah Teknik Mesin Unlam*, Vol. 2, No. 2, hh 76
- Devadassan, S 2012, "Investigation of Performance Efficiency on the Effect of Wet Scrubber Inlet Dimensions," *International Journal of Computer Applications*, Vol 4, No. 3, hh 43
- Hanif, M 2012, “Pengaruh Laju Alir Gas Dan Cairan Pada Absorpsi Gas CO<sub>2</sub> Oleh H<sub>2</sub>O Dalam Packed Column”, *Prosiding SNSMAIP*, Vol. 1, No. 144, Hh 166
- Kern, D (1983), *Process Heat Transfer*, Mc Graw Hill Company Inc, Tokyo
- Lee, C 2021, “Parametric analysis and design optimization of wet SO<sub>x</sub> scrubber system in marine industry”, *Elsevier*, Vol. 3, No. 55, hal 20
- Mach, 2020, *Guide to Wet Scrubber Maintenance*, Mach Engineering LLC, Texas
- Meikap , B.C. and Biswas , M.N. 2004 . Fly-ash removal efficiency in a modified multi-stage bubble column scrubber . *Separ. Purif. Technol* , 36 : 177 – 190
- Mc.Cabe, Warren L (1991), *Unit Operations of Chemical Engineering Fifth Edition*, Mc Graw Hill, New York
- Mukherjee, R 1998, *Effectively Design Shell-and-Tube Heat Exchangers*, India, Engineers India Ltd.
- Permanadewi, I 2021, “Analisis Pengaturan Temperatur, Konsentrasi, dan Waktu Pengadukan pada Tekanan Atmosferik untuk Meningkatkan Kepresisian Densitas Larutan Alginat”, *Teknik*, 42 (1), hal 29-34
- Petrokimia Gresik, 2023, *Petrokimia Gresik Solusi Agroindustri*, diakses pada 19 September 2023, petrokimia-gresik.com
- Pollock . 1966 . “ Removal of SO<sub>2</sub> and fly ash from coal burning power plant flue gas ” . In *ASME Meeting*



- 
- Raj Mohan , B. and Meikap , B.C. 2009 . “Performance studies of the particulate scrubbing in a novel spray-cum-bubble column scrubber” . *Chem. Eng. Res. Design* , [87](#) : 109 – 118
- Walikrom, R (2018) ‘Studi Kinerja plate heat exchanger pada sistem pendingin PLTGU’, *Jurnal Teknik Mesin*, 1(1), hh. 40