



DAFTAR PUSTAKA

- Du, R. dkk. (2018) “Enhanced enzymatic hydrolysis of corncob by ultrasound-assisted soaking in aqueous ammonia pretreatment,” *3 Biotech*, 8(3), hal. 1–7. Tersedia pada: <https://doi.org/10.1007/s13205-018-1186-2>.
- Egata, dkk. (2017) “National Conference Proceeding on Waste Treatment Technology Pengaruh Waktu Delignifikasi terhadap Karakteristik Selulosa dari Daun Nanas dan Jerami,” in National Conference Proceeding on Waste Treatment Technology, hal. 59–64.
- Fadly Khaira, Z. dkk. (2015) “Pembuatan Bioetanol dari Limbah Tongkol Jagung Menggunakan Proses Simultaneous Sacharification and Fermentation (SSF) dengan Variasi Konsentrasi Enzim dan Waktu Fermentasi,” *JOM FTEKNIK*, 2(2), hal. 1–8.
- Fakayode, O.A. dkk. (2020) “Novel two-pot approach ultrasonication and deep eutectic solvent pretreatments for watermelon rind delignification: Parametric screening and optimization via response surface methodology,” *Energy*, 203. Tersedia pada: <https://doi.org/10.1016/j.energy.2020.117872>.
- Fitriani, Bahri, S. dan Nurhaeni (2013) “Produksi Bioetanol Tongkol Jagung (Zea Mays) dari Hasil Proses Delignifikasi,” *Journal of Nature Science*, 2(3), hal. 66–74.
- Fitriani, F. dkk. (2018) “KANDUNGAN SELLULOSA, HEMISELLULOSA DAN LIGNIN PAKAN KOMPLIT BERBASIS TONGKOL JAGUNG YANG DISUBSTITUSI Azolla pinnata PADA LEVEL YANG BERBEDA,” *Jurnal Galung Tropika*, 7(3), hal. 220. Tersedia pada: <https://doi.org/10.31850/jgt.v7i3.365>.
- Hidayat, M.R. (2013) “Teknologi Pretreatment Bahan Lignoselulosa,” *Biopropal Industri*, 4(1), hal. 33–48.
- Kanani, N. dkk. (2018) “Proses Delignifikasi Dengan Metode Pre-Treatment Kimia,” *Jurnal TEKNIKA*, 14(1), hal. 1–10.



Laporan Hasil Penelitian
Pengolahan Tongkol Jagung Menjadi Selulosa Menggunakan Pelarut
NaOH dengan Bantuan Ultrasonik

- Kininge, M.M. dan Gogate, P.R. (2022) “Intensification of alkaline delignification of sugarcane bagasse using ultrasound assisted approach,” *Ultrasonics Sonochemistry*, 82, hal. 105870. Tersedia pada: <https://doi.org/10.1016/j.ultsonch.2021.105870>.
- Lestari, M.D., Sudarmin dan Harjono (2018) “Ekstraksi Selulosa dari Limbah Pengolahan Agar Menggunakan Larutan NaOH sebagai Prekursor Bioetanol,” *Indonesian Journal of Chemical Science*, 7(3), hal. 236–241. Tersedia pada: <http://journal.unnes.ac.id/sju/index.php/ijcs>.
- Li, X. dkk. (2018) “Quantitative visualization of lignocellulose components in transverse sections of moso bamboo based on ftir macro- and micro-spectroscopy coupled with chemometrics,” *Biotechnology for Biofuels*, 11(1), hal. 1–16. Tersedia pada: <https://doi.org/10.1186/s13068-018-1251-4>.
- Loow, Y.L. dan Wu, T.Y. (2018) “Transformation of oil palm fronds into pentose sugars using copper (II) sulfate pentahydrate with the assistance of chemical additive,” *Journal of Environmental Management*, 216, hal. 192–203. Tersedia pada: <https://doi.org/10.1016/j.jenvman.2017.04.084>.
- Mardina, P. dkk. (2013) “Tongkol Jagung Dengan Hidrolisis Asam Encer,” *Journal Konversi*, 2(2), hal. 17–23.
- Nhu, L.T. dan Kieu, L.T. Van (2014) “Study of Ultrasonic Technique Application to Enhance The Pretreatment Efficiency of Bioethanol Production From Sugarcane Bagasse,” *Journal Science and Technology*, 1(12), hal. 106–109.
- Nurwahdah dkk. (2018) “Pretreatment Lignoselulosa dari Jerami Padi dengan Deep Eutectic Solvent untuk Meningkatkan Produksi Bioetanol Generasi Dua,” *Jurnal Riset Industri Hasil Hutan*, 10(1), hal. 43–54.
- Olughu, O.O., Tabil, L.G. dan Dumonceaux, T. (2021) “Ultrasonic Delignification and Microstructural Characterization of Switchgrass,” *Energies*, 14(263), hal. 1–17.
- Patil, R.S., Joshi, S.M. dan Gogate, P.R. (2019) “Intensification of delignification of sawdust and subsequent enzymatic hydrolysis using ultrasound,”



Laporan Hasil Penelitian
Pengolahan Tongkol Jagung Menjadi Selulosa Menggunakan Pelarut
NaOH dengan Bantuan Ultrasonik

Ultrasonics Sonochemistry, 58(April). Tersedia pada:
<https://doi.org/10.1016/j.ultsonch.2019.104656>.

Pejin, D.J. dkk. (2012) "Increase in bioethanol production yield from triticale by simultaneous saccharification and fermentation with application of ultrasound," Journal of Chemical Technology and Biotechnology, 87(2), hal. 170–176. Tersedia pada: <https://doi.org/10.1002/jctb.2675>.

Pejin, D.J. dkk. (2012) "Increase in bioethanol production yield from triticale by simultaneous saccharification and fermentation with application of ultrasound," Journal of Chemical Technology and Biotechnology, 87(2), hal. 170–176. Tersedia pada: <https://doi.org/10.1002/jctb.2675>.

Poon, J.J., Tan, M.C. dan Kiew, P.L. (2020) "Ultrasound-assisted extraction in delignification process to obtain high purity cellulose," Cellulose Chemistry and Technology, 54(7–8), hal. 725–734. Tersedia pada: <https://doi.org/10.35812/CelluloseChemTechnol.2020.54.72>.

Ranjha, M.M.A.N. dkk. (2021) "Sonication, a potential technique for extraction of phytoconstituents: A systematic review," Processes, 9(8), hal. 1–21. Tersedia pada: <https://doi.org/10.3390/pr9081406>.

Ruhibnur, R. dkk. (2019) "Optimization of Corncob Waste in Bioethanol Manufacturing and Its Characteristics by the Treatment of Fermentation Period and Yeast Concentration," Jurnal Teknologi Agro-Industri, 6(2), hal. 82–91.

Sabaruddin, F.A. dkk. (2023) "Emerging trends in the appliance of ultrasonic technology for valorization of agricultural residue into versatile products," Ultrasonics Sonochemistry, 99(June), hal. 106572. Tersedia pada: <https://doi.org/10.1016/j.ultsonch.2023.106572>.

Subhedar, P.B. dan Gogate, P.R. (2014) "Alkaline and ultrasound assisted alkaline pretreatment for intensification of delignification process from sustainable raw-material," Ultrasonics Sonochemistry, 21(1), hal. 216–225. Tersedia pada: <https://doi.org/10.1016/j.ultsonch.2013.08.001>.



Laporan Hasil Penelitian
Pengolahan Tongkol Jagung Menjadi Selulosa Menggunakan Pelarut
NaOH dengan Bantuan Ultrasonik

- Sugiarto, Y. dkk. (2014) "Pengaruh Frekuensi Ultrasonik dan Konsentrasi Naoh pada Proses Pretreatment Bioetanol Pelepas Sawit," *Jurnal Teknologi Pertanian*, 15(3), hal. 213–222.
- Susmiati, Y. (2018) "Prospek Produksi Bioetanol dari Limbah Pertanian dan Sampah Organik The Prospect of Bioethanol Production from Agricultural Waste and Organic Waste," *Jurnal Teknologi dan Manajemen Agroindustri*, 7(2), hal. 67–80. Tersedia pada: <https://doi.org/10.21776/ub.industria.2018.007.02.1>.
- Trisanti, P.N. dkk. (2018) "Gergaji Kayu Sengon Melalui Proses Delignifikasi Alkali Ultrasonik," *Sains Materi Indonesia*, 19(3), hal. 113–119.
- Umindya, G. dkk. (2019) "Pembuatan dan Karakterisasi Selulosa dari Limbah Serbuk Meranti Kuning (*Shorea macrobalanos*)," *Jurnal Sain Terapan*, 5(1), hal. 142–147.
- Ur Rehman, M.S. dkk. (2012) "Use of ultrasound in the production of bioethanol from lignocellulosic biomass," *Energy Education Science and Technology Part A: Energy Science and Research*, 30(SPEC .ISS.1), hal. 359–378.